


nome market.



A complete Somfy J4 offer

> Take advantage of a dynamic market for External Venetian Blinds

Somfy J4 motorizations offer a complete range that uses all transmission technologies. Take advantage of all the opportunities of a dynamic market whether for the residential or commercial building sectors.

> Your choice is simpler

- J4 io adapts to all External Venetian Blinds sizes. • Parallel installation possible regardless of the number standards for External Venetian Blinds.
- No fiddly wires for the control points.
- Rapid installation so the site remains clean and the walls are damage-free.


14 RANGE. SOMFY'S EXCLUSIVE OFFERS, MAKING A REAL DIFFERENCE FROM THE FACTORY TO THE SITE $^\circ$



The mushroom control, adjustable up-down: greater integration and installation flexibility.

- Easy to fit into all boxes on the market (boxes open at the top and at the bottom).
- The motor and Venetian blind are always protected even if an error occurs in handling

Inversion of the direction of the rotation using the remote control makes adjustments simple, with no need to access the motor.



J4 io complies with the market's ergonomic The process to set limits is universal, both in the factory and on your sites.

io-homecontrol® motorization for External Venetian Blinds

With Somfy, enjoy an exclusive offer



J4 io



New J4 io Your External Venetian Blinds now available on the intelligent



With io-homecontrol®, Somfy products can communicate and are interoperable with each other and products from other major home installation brands.

With the new motorization of the External Venetian Blinds J4 io, you can deploy a complete io-homecontrol® offer on all of your markets.

io-homecontrol[®], the new radio standard for the home

With the new motorization for External Venetian Blinds, Somfy now offers the io-homecontrol® technology with all its Home Motion products. Somfy shares this radio standard for the entire home with other major home installation brands.

Simpler and less expensive to install, easier to upgrade according to customers needs, guaranteeing interoperability over the long term between different products offered by home installation groups, positioning **io-homecontrol**® as the leader in wireless home automation.

NEW J4 io. SOMFY'S EXCLUSIVE OFFERS, MAKING A DIFFERENCE ON THE MARKET



For your clients, io-homecontrol® is synonymous with home automation that is easily accessible, upgradeable and simple to control, even remotely.

> Control via the internet TaHoma® is a simple, user-friendly This means not only that the order has been transmitted, but interface to programme, monitor also that it has been executed. and control all of a home's

The occupant knows the status of io-homecontrol® products their equipment (on/off)

With **TaHoma®**, the occupant can control the position of the External Venetian Blinds and choose a precise positioning for the slats.



Somfy has you in mind, starting with integration



Somfy has always been very attentive to respecting your work habits and helping you save time. The new Somfy **J4 io** proves this once again.

A process over which you have full control

The shortest motor on the market for your External Venetian Blinds

- The motors delivered are already customised to suit the shape of your boxes.
- End-limit settings are handled in the factory.
- The io plate is assembled rapidly, requiring just three steps thanks to fast connections.
- No specific training of the operator is required, and ergonomics are identical to market standards.
- Compatible with all existing accessories.

J4 io, the solution for all your projects

- The shortest motor on the market to motorize the narrowest Venetian blinds.
- A motor that adapts to all assembly configurations and the size of your Venetian blinds.



Save time with the Push & Forget function

In settings mode, you no longer need to press on the key while waiting for the lowest point to move up to the highest point. Just press once: the operator can move along to another task.

J4 io range technical data sheet. Test done at 20°C, 230V, 50Hz.

	N.m	rpm	mm	W	А	min		kg						
Designation	Nominal torque	Speed with load	L1 max.	L2 min.	L3 max.	L4 max.	L5 min.	L6 max.	Section	Rated power	Rated current	Thermal time	Brake type	Weight (+adapter)
J4 06 io	6	24	254	47	222	306	16	265	55x58	95	0.5	6	Sliding	1.5
J4 10 io	10	24	269	47	237	321	16	280	55x58	110	0.6	6	Sliding	1.7
J4 18 io	18	24	289	47	257	341	16	300	55x58	155	0.8	6	Sliding	2.7
J4 io plate	I	1	195	1	1	1	1	1	26x19	0.4	<0.03	1	1	0.24

Somfy: installation with a difference

With Somfy, offer all the advantages of motorized, automated External Venetian Blinds



Like all Somfy motorization, **J4 io** intends to make the work of the installer simple and secure, thereby guaranteeing a rapid, high quality start-up.

Rapid installation

- **Automatic mode:** once connected to the mains, **J4 io** automatically conducts a high stop detection cycle ... and the settings are done!
- Easy resetting: settings are adjusted with the remote control. The ergonomics are common to all of the market's adjustable sun shade motors.

Thanks to io-homecontrol[®], more secure use

- **To make installation easier,** the remote control screen guides the installer through each step of the start-up process. No additional expertise is required for proper installation.
- You can easily name a motor, select a motor to link it to a control unit, unlink it, programme it, cancel the programming, or even change its direction of rotation, even during installation.



Customisation of the positioning for Venetian blinds

- Your clients always find the slats in their proper position.
- Settings are adjusted using the Situo Mobile VB io remote control (a default setting is already integrated into the motor).

Offer your clients motorization and automation solutions for their External Venetian Blinds. Thanks to the exclusive functions of the **io-homecontrol**® technology, your clients will take maximum advantage of their installation to control their comfort and security at all times.



> Visual comfort

Using the **Situo Mobile VB io** remote control (also compatible with roller shutters), the slats adjust to modulate natural light, eliminate glare and protect the inside from the sun. With one click on the «my» key, they return to their favourite position.



> Thermal comfort

The automatic devices command the position of the External Venetian Blinds to maintain a pleasant temperature in all four seasons. In the summer, the sun sensor lowers them to keep the inside of your home cool. In the winter, the clock raises the External Venetian Blinds during the day to take advantage of the sun's heat.



> Privacy

The external Venetian's slats adjust to protect the privacy of your home, while letting natural light in. This position can be controlled manually using the **Situo Mobile VB io** or **TaHoma®** via scenarios or time programming function.



> Security

The home's External Venetian Blinds participate in presence simulation scenarios that can be programmed with the **TaHoma**® interface. They move automatically according to defined schedules, leading potential intruders to believe that the house is occupied.

In residential, customise your installations

Range of io control units and automatic devices



Smoove 1 io

- · Wall-mounted, sensitive, single-channel control unit
- Up, down, stop
- "My" favourite position



Situo Mobile VB io

- Remote control for one product or one group of products Tilting slats function for External Venetian Blinds
- Compatible with roller shutters • 1 channel
- Up, down, stop, tilting slats
- "My" favourite position




Façade remote control

- for summer comfort 4 manual channels
- + 1 automatic sun device
- Feedback function

• "My" favourite position

Sunis WireFree™ io Eolis WireFree™ io • Completely wireless sun sensor







TaHoma® Box for TaHoma® Connect

• Setting the sensitivity threshold

When connected to an ADSL router, the TaHoma® Box allows you to control all home equipment from within the home or remotely via a PC, smartphone or tablet. TaHoma® Connect is compatible with both io-homecontrol® and RTS and will be soon capable of controlling almost all available radio protocols.



	N.m	rpm	mm	W	Α	min		kg						
Designation	Nominal torque	Speed with load	L1 max.	L2 min.	L3 max.	L4 max.	L5 min.	L6 max.	Section	Rated power	Rated current	Thermal time	Brake type	Weight (+adapter)
J4 06 io	6	24	254	47	222	306	16	265	55x58	95	0.5	6	Sliding	1.5
J4 10 io	10	24	269	47	237	321	16	280	55x58	110	0.6	6	Sliding	1.7
J4 18 io	18	24	289	47	257	341	16	300	55x58	155	0.8	6	Sliding	2.7
J4 io plate	1	I	195	1	I	I	I	I	26x19	0.4	<0.03	1	1	0.24



All Somfy products are tested during production. Somfy guarantees its products for five years for its installer and manufacturer clients.





< Situo Mobile VB io remote control