

Power Supply 320 mA

animeo Solo

animeo IB+

animeo KNX

animeo LON

SOLUTIONS FOR COMMERCIAL BUILDINGS



Ref. 9018244

KNX Power Supply with integrated choke. Worldwide usable due to wide range input 100 – 240 VAC. LED indicator for Power, Overload and Reset. Push button for automatic reset on the KNX line. Additional auxiliary voltage output with 30 VDC. Nominal current on the short circuit protected outputs is 320 mA.

Technical features:

- Wide range input 100 to 240 VAC / 50-60 Hz
- Integrated KNX choke
- Integrated KNX reset function for choked output
- Short circuit protection
- Status LEDs for Power, Overload and Reset

CHARACTERISTICS

Supply voltage	100-240 V AC / 50/60 Hz	
Output voltage	30 V DC (28-31 V DC according to KNX specification)	
Output voltage not choked	30 V DC	
Nominal current	320 mA	
Terminals	Screw terminal max. 2,5 mm ² cross section	KNX bus terminal/auxiliary voltage terminal Ø 0,6 - 0,8 mm
Ambient temperature	- 5 °C to + 50 °C	
Protection class	IP 20	
Mounting	DIN rail	
Dimensions	4 modules 71 x 91 x 62 mm (w x h x d)	
Conformity	www.somfy.com/ce	

